



TALKAPHONE


ETP-GP SERIES GOOSENECK PEDESTAL MOUNT

TALKAPHONE'S FREE
STANDING GOOSENECK
PEDESTAL MOUNT ALLOWS AN
EMERGENCY / INFORMATION OR
ACCESS CALL STATION TO BE
MOUNTED AT BOTH CAR AND
TRUCK HEIGHT PRACTICALLY
ANYWHERE. THE GOOSENECK
MOUNT IS IDEAL FOR DRIVE-
UP APPLICATIONS INCLUDING
PARKING GARAGE ACCESS
CONTROL AND ENTRY.

FEATURES

- Constructed of 1/8" thick steel
- Mount any Talkaphone surface mount with any call station
- Standard pedestal is painted safety yellow
- Vandal-resistant structure and coating designed to resist extreme weather conditions
- A variety of signage, graphics, and color choices are available
- Easily mount any Talkaphone ETP-500 Series, VOIP-200, VOIP-500, or VOIP-600 Series call station into the unit (sold separately).
- ADA-compliant



GENERAL SPECIFICATIONS	ETP-GP SERIES GOOSENECK PEDESTAL
Construction:	2" (51mm) O.D., 1/8" thick steel with multi-coat rust-inhibitive coating
Mounting:	Mounts into concrete foundation using included hardware (shipped in advance). Mounting options available for pre-poured parking decks.
Power Source:	ETP-500 Series (sold separately) are powered by a phone line; VOIP-200 Series (sold separately) are powered by 12VDC, 24VAC/DC or PoE; VOIP-500 Series (sold separately) are powered by 12VDC, 24VAC/DC or PoE; VOIP-600 Series (sold separately) are powered by 12VDC, 24VAC/DC or PoE
Coating	High-gloss, multi-layer, corrosion-inhibitive system with resistance to UV-fade and graffiti protection
Colors	Safety yellow is standard. Available in a variety of colors.
Call Station Options	VOIP-200, 500, and 600 Series IP Call Stations; ETP-500 Series Analog Call Stations
Approvals	ETL Recognized Component -- Conforms to UL Standards 60950-1 and 60950-22. Certified to CSA Standard C22.2 Nos. 60950-1 and 60950-22. 



*Accessories on Page 4


All specifications are subject to change without notice.

TALKAPHONE LLC LIMITED WARRANTY

Talkaphone LLC warrants Talkaphone Emergency Phone, Wide-Area Emergency Broadcast System (WEBS®), and Area of Rescue equipment against any defects in material and workmanship, under normal use, for a period of twenty-four (24) months from date of installation, provided that Talkaphone receives a completed "Installation Certification" certifying the date on which the system has been installed. An "Installation Certification" card is enclosed with every unit. In the event that no "Installation Certification" is received by Talkaphone, the twenty-four (24) months will commence on the date of shipment by Talkaphone. Warranty period for Models ETP-MT Tower, ETP-MT/R Radius Tower, WEBS-MT/R Radius Tower, WEBS-PM Pedestal Mount, and ETP-PM Pedestal Mount is five (5) years, under the same terms and conditions. Warranty period for Intercommunication Products is three (3) months, under the same terms and conditions. In the event this product is found by Talkaphone to be defective within the warranty period, Talkaphone's only obligation and your exclusive remedy, shall be the repair and/or replacement of any defective parts, provided the equipment is returned to Talkaphone LLC., 7530 N. Natchez Ave., Niles, IL 60714. It is expressly understood that Talkaphone shall have no obligation to furnish labor, nor pay for the labor of any third parties, nor bear the expense of shipping defective products for repair. This warranty shall not apply if Talkaphone determines that the defect was caused by improper use or installation, or damage caused to the equipment by others.

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

	ETP-GP-C	ETP-GP-T
		
Model:	ETP-GP-C: Car height gooseneck pedestal mounting option	ETP-GP-T: Truck height gooseneck pedestal mounting option
Dimensions (W x H x D):	7.5 x 41.25 x 12.5 in. (190.5 x 1048 x 317.5 mm)	7.5 x 71.25 x 12.5 in. (190.5 x 1810 x 317.5 mm)
Weight	20 lbs. (9.1 kg)	30 lbs. (13.6 kg)

	ETP-GP-D
	
Model:	ETP-GP-D: Dual car and truck height gooseneck pedestal mounting option
Dimensions (W x H x D):	7.5 x 71.25 x 12.5 in. (190.5 x 1810 x 317.5 mm)
Weight	34 lbs. (15.4 kg)

All specifications are subject to change without notice.

BUILD YOUR GOOSENECK PEDESTAL

PICK YOUR BASE:

ETP-GP-C



ETP-GP-T



ETP-GP-D



PICK YOUR SURFACE MOUNT:

ETP-SM-1



ETP-SMH-1



ETP-SML



ETP-SMCR



PICK YOUR CALL STATION:

VOIP-200 SERIES

*Must also order
ADAPT-2-56 or ADAPT-2cam-56




*ADAPT-2-56



*ADAPT-2CAM-56


ETP-500 SERIES VOIP-500 Series



VOIP-600 SERIES



DIMENSIONAL DRAWING



TALKAPHONE

THE LEADERS IN SECURITY AND LIFE SAFETY COMMUNICATIONS

*All dimensions are in inches and
are provided for reference only.*