



## WEBS-PA-2A Area Paging Unit – Installation Instructions

### I. Introduction

Model WEBS-PA-2A Area Paging Units are designed to mount on a wall or pole, for use with a WEBS-ZPS as part of an analog Wide-area Emergency Broadcast System. The amplifier requires 120VAC, 60Hz, with 48 watts maximum power consumption.

### II. Wall Mounting

The Area Paging Unit is held to the wall with 4 #10 screws. Remove the cap, then remove from the front wrap from the back mounting plate. Install two #10 screws in order to hold the top section of the back plate to the wall. Note that the screws should be located so that the Area Paging Unit will be at the desired height and in the correct position to receive any conduit connections.

Mount the back plate on the wall using the two keyholes on the top rear of the unit to the two screws mounted to the wall. Install two additional #10 screws of the appropriate type in the holes in the lower portion of the back plate. Tighten all four screws.

### III. Pole Mounting

For pole mounting, model **ETP-PMKT** Pole Mount Kit is recommended to strap the unit to a pole. Model **ETP-PMKT-TOOL** is the required tool. Other banding solutions are also available.

### IV. Wiring

Electric power and the paging line can be brought into the unit in one of two ways:

1. There are two large openings in the back of the unit to allow the unit to be mounted over a flush mounted standard electrical outlet box and/or flush mounted telephone connector box.
2. There are two conduit openings available on the bottom of the unit for connection of power and/or paging line.

Install conduit to hole(s) in bottom of unit, if this method is being used, and bring power line and/or paging line to inside of unit.

The amplifier and horns are installed prior to shipment. Simply connect the tip (green) and ring (red) wires (grounding is also desirable) to your line coming from the WEBS-ZPS or WEBS-ZPM-9 Zone Paging System, and then re-attach the front wrap and cap.

### V. Programming

Program the Amplifier as shown in the WEBS-ZPS manual. The amplifier volume level is pre-set but you may adjust as desired with a flat-head screwdriver. If you are mounting the Area Paging Unit high off the ground for broadcasting over great distances, **be extremely careful before turning the volume up—ear protection is strongly recommended.** The Area Paging Unit is capable of reaching sound levels well above 110dBA.

Copyright 2009 Talk-A-Phone Co. All rights reserved.

Talk-A-Phone Co. • 7530 North Natchez Avenue • Niles, Illinois 60714-3804  
Phone 773.539.1100 • Fax 773.539.1241 • info@talkaphone.com • www.talkaphone.com

All prices and specifications are subject to change without notice.

Talk-A-Phone, Talk-A-Lert, Scream Alert and WEBS are registered trademarks of Talk-A-Phone Co.

Rev. 7/27/09